



### MODEL P-PU225



| TİP<br>MODEL                 | Çalışma ortamı<br>Operating medium | Hareket modeli<br>Motion Pattern | A     | B     | C     |
|------------------------------|------------------------------------|----------------------------------|-------|-------|-------|
| P-PU225-15A<br>P-PU225SS-15A | Hava , su , yağ<br>Air water ,oil  | Pilot Type                       | 66,5  | 106,5 | 48,0  |
| P-PU225-20A<br>P-PU225SS-20A |                                    |                                  | 96,0  | 126,0 | 70,0  |
| P-PU225-25A<br>P-PU225SS-25A |                                    |                                  | 96,0  | 126,0 | 70,0  |
| P-PU225-35A<br>P-PU225SS-35A |                                    |                                  | 131,0 | 145,5 | 96,0  |
| P-PU225-40A<br>P-PU225SS-40A |                                    |                                  | 131,0 | 145,5 | 96,0  |
| P-PU225-50A<br>P-PU225SS-50A |                                    |                                  | 160,0 | 160,5 | 112,0 |

### ÖLÇÜLER VE TEKNİK AÇIKLAMA / SIZES AND TECHNICAL EXPLANATION

| Tip / Model | Bağlantı<br>Portu<br>Connection<br>Port | Orifis<br>Orifice<br>( Ø mm ) | Tip / Type        | Max.<br>Basınç<br>Max.<br>Pressure<br>( Bar ) | Çalışma<br>Basıncı<br>Operating<br>pressure<br>( Bar ) | Ortam<br>Akışkanlığı<br>Medium<br>Viscosity | Çalışma<br>Sıcaklığı<br>Operating<br>Temp | Çalışma Tipi<br>Operating Type                           | Anma Voltajı<br>Rated voltage | Cv Değeri<br>Cv Value |
|-------------|-----------------------------------------|-------------------------------|-------------------|-----------------------------------------------|--------------------------------------------------------|---------------------------------------------|-------------------------------------------|----------------------------------------------------------|-------------------------------|-----------------------|
| P-PU225-15A | 1/2"                                    | 13                            | Normally<br>Close | 15 Bar                                        | 0,5~10                                                 | <50CST                                      | -5+80 °C                                  | Direkt hareket<br>Diyafram<br>Direct action<br>Diaphragm | DC12-24V<br>AC24V-380V        | 4.5                   |
| P-PU225-20A | 3/4"                                    | 25                            |                   |                                               |                                                        |                                             |                                           |                                                          |                               | 12                    |
| P-PU225-25A | 1"                                      | 25                            |                   |                                               |                                                        |                                             |                                           |                                                          |                               | 12                    |
| P-PU225-35A | 1 1/4"                                  | 38                            |                   |                                               |                                                        |                                             |                                           |                                                          |                               | 22                    |
| P-PU225-40A | 1 1/2"                                  | 38                            |                   |                                               |                                                        |                                             |                                           |                                                          |                               | 30                    |
| P-PU225-50A | 2"                                      | 50                            |                   |                                               |                                                        |                                             |                                           |                                                          |                               | 48                    |

PNÖSAN San ve Tic. Ltd. Şti.

Merkez : Cemaliye Mah.Gazi Çeşme Sok.No:2/A 59860 Çorlu / TEKİRDAĞ Tel:(+90 282) 652 94 86 Pbx Fax:(+90 282) 652 74 05

Fabrika : Zafer Mah.Şehit Yzb.Yücel Kenter Cad. Blok 7 No:1-2-3 Çorlu/Tekirdağ

www.pnosan.com / bilgi@pnosan.com / satis@pnosan.com